

Conex | Bänninger
Series 8000



A range of yellow brass threaded fittings.

Features and benefits:

- Available in sizes 1/8 - 2".
- Manufactured to EN 1254-4.
- The threads are manufactured to ISO 228-1.
- Suitable to material with EN 12165, CW617N, EN 12164 and CW617N.

- Hydraulic working temperatures and pressures:

Size (inches)	Working pressure (bar)	
	-20 °C to 120 °C	120 °C to 225 °C
1/4 to 3/4	25	16
1 to 2	16	10
2 to 4	10	6



Series 8000 range

<p>Brass Plug Male Thread (Parallel)</p>	<p>Female Elbow Female x Female Thread</p>	<p>Male x Female Elbow Male x Female Thread</p>	<p>Tee - Equal Female Thread All Ends</p>
			
<p>8595 From: 1/4" To: 2"</p>	<p>8090 From: 1/4" To: 3/4"</p>	<p>8092 From: 3/8" To: 1"</p>	<p>8130 From: 1/4" To: 1"</p>
<p>Reduced Bush Male x Female Thread</p>	<p>Straight Coupler Female x Female Thread</p>	<p>Hexagon Nipple Male x Male Thread</p>	<p>Flanged Backnut</p>
			
<p>8241 From: 3/8 x 1/4" To: 2 x 1 1/2"</p>	<p>8270 From: 1/4" To: 2"</p>	<p>8280 From: 1/8" To: 2"</p>	<p>8310 From: 1/2" To: 2"</p>
<p>Barrel Nipple Male Thread x Length (mm)</p>	<p>Running Nipple Male (Parallel)</p>	<p>Blank Cap Female Thread</p>	
			
<p>8530 From: 3/8" x 40 mm To: 2" x 100 mm</p>	<p>8531 From: 1/4" To: 3/4"</p>	<p>8599 From: 1/4" To: 2 1/2"</p>	

*Conex|Bänninger products are approved by numerous Standards Authorities and Certification Bodies. For more details on this product range, please email our technical team at: technical@ibpgroup.com.

Conex Universal Limited: Global House, 95 Vantage Point, The Pensnett Estate, Kingswinford, West Midlands DY6 7FT, UNITED KINGDOM.
 Tel: +44 (0)121 557 2831 | Fax: +44 (0)121 557 0185 | Email: sales@ibpgroup.com | Website: www.conexbanninger.com

This is a representation of the full range from Conex Universal. IBP trade marks are registered in numerous countries.